



## TVS

### FEATURES

- Digital display of temperature, alarms, and settings
- Two independent variable speed stages (7.5 FLA each)
- One relay stage (6 FLA) Heat/Cool
- Seven factory program settings can be easily changed by the user
- Internal memory is retained during power failure
- Alarm relay to signal high or low temperature, power interruption, or low line voltage
- Extendable temperature sensor
- 115 or 230V AC operation
- 2 year limited warranty



## SEC-HD

### FEATURES

- Digital display of temperature, alarms, and settings
- Heavy duty relays
- Two variable speed stages (10 FLA each)
- Three stages that can be used for heating or cooling (6 FLA each)
- ON indicator lights for each stage
- Digital temperature display with four digit accuracy
- Internal memory retention during a power failure
- Alarm relay to signal high or low temperature, power interruption or low line voltage
- Extendable temperature sensor
- 115 or 230V AC operation
- 2 year limited warranty



## PEC +

### FEATURES

- Digital display of temperature, alarms, and settings
- User configurable Growth Curve, can be set up to 315 days
- Two variable stages (7.5 FLA)
- Three fixed heat/cool stages (4.4 FLA @ 115 VAC or 2.2 FLA @ 230 VAC)
- High or low alarm contact for an external alarm
- Fixed stages can be used as duty cycle timers
- Can control an inlet actuator
- Stage 5 can operate as a proportional interval control
- Internal memory retention during a power failure
- Extendable temperature sensor
- Electrical rating: 115/230V AC
- 2 year limited warranty

